



## Male and female DC12V plug for security, positive and negative 5.5\*2.1mm terminal type DC male and female plug

High quality engineering grade DC power supply female plug, connector specification is 5.5mm\*2.1mm/2.5mm. Alloy (fire-extinguishing flower) butt joint, the tail adopts anti-skid screw, tighten the contact well, the wiring does not fall off.

The joint JUE edge plastic adopts new environmental protection and fireproof material, with smooth appearance: "no conjoined glue" and "no small hole", non-recycling inferior JUE edge glue!

### Product parameters:

1. DC head conversion of transmission wire, universal DC port conversion of monitoring camera is adopted.
2. Product specifications: the core of the product line is thick, which can withstand 12v-36v voltage. The outer skin is made of plastic and other materials. Color: green and black.
3. Green rubber stick is marked with + - positive and negative poles.
4. Transmission voltage: 5v-38v
5. Transmission power: 80W
6. With shrapnel interface, 20A line contact will not generate sparks! Quality products, conscience quality, to avoid inferior brought hidden trouble!
7. The plug shall be protected by a non-magnetic enclosure
8. This product is made of environmental friendly materials in accordance with RHOS standard, which can withstand various complex environments and resist corrosion.

Scope of application: security, monitoring equipment, LED lamp, converter and other equipment  
2.1mmDC power output and input connection