



I LY-CM / LY-CH

Male and Female Connector



Male and female LY-CM y LY-CH plug for security, positive and negative 5.5*2.1mm terminal type DC male and female plug.

High quality engineering grade DC power supply female plug, connector specification is 5.5mm*2.1mm/2.5mm. Alloy (fire-extinguishing flower) butt joint, the tail adopts anti-skid screw, tighten the contact well, the wiring does not fall off. The joint JUE edge plastic adopts new environmental protection and fireproof material, with smooth appearance: "no conjoined glue" and "no small hole", non-recycling inferior JUE edge glue!

PRODUCT PARAMETERS:

1.DC head conversion of transmission wire, universal DC port conversion of monitoring camera is adopted.

2.Product specifications: the core of the product line is thick, which can withstand 12v-36v voltage. The

outer skin is made of plastic and other materials. Color: green and black.

3.Green rubber stick is marked with + - positive and negative poles.

4.Transmission voltage: 5v-38v.

5.Transmission power: 80W.

6.With shrapnel interface, 20A line contact will not generate sparks! Quality products, conscience quality, to avoid inferior brought hidden trouble!

7.The plug shall be protected by a non-magnetic enclosure.

8.This product is made of environmental friendly materials in accordance with RHOS standard, which can withstand various complex environments and resist corrosion.

Scope of application: security, monitoring equipment, LED lamp, converter and other equipment 2.1mmDC power output and input connection.